

## 0702L 7-inch LCD

**Touchscreen Monitor** 





Edge-to-edge design with integrated 10-touch



**3-Year Warranty** 



Commercial-grade

## **Product Overview**

The Elo 0702L 7-inch touchscreen monitor delivers a professional-grade interactive solution with Elo's industry-leading TouchPro® PCAP technology featuring edge-to-edge glass and enabling up to 10 simultaneous touches. Backed by a three-year warranty, the feature rich touchscreen monitor is equipped with DisplayLink technology - enabling connectivity for power, video and touch over a single cable. With a compact form factor measuring just over half an inch thin and a clean design made for simple integration, the 0702L is ideal for customer facing point of interaction installations in point-of-sale, brand loyalty, point of information, signage and hospitality applications. With a minimal footprint, the 0702L is also well-suited for industrial kitchen equipment controllers.

DisplayLink technology provides touch, video and power connectivity over a single cable

Touchscreen is compatible with use of finger, glove and stylus

Integrate with ease - From stands and pole mounts to shelf mounts, wall mounts and 3rd party VESA mounts

## **0702L 7-inch LCD Touchscreen Monitor**

Specifications					
Color	Black				
Diagonal Size	7" / 177.8 mm				
Active Touch Area	6.07" x 3.38" / 154.08 mm x 85.92 mm				
LCD Technology	ive matrix TFT LCD				
Touch Technology	TouchPro PCAP				
Number of Touches	10 Touches				
Aspect Ratio	5:3				
Native Resolution	800 x 480				
Preset Video Timings	800 x 480 60 Hz				
Number of Colors	16.2M				
Brightness (typical)	Panel: 500 nits; with TouchPro PCAP: 430 nits				
Response Time (Tr + Tf) (typical)	25 msec				
Viewing Angle (typical)	Horizontal: 75° or 150° total; Vertical: 55°/65° or 120° total				
Contrast Ratio (typical)	500:1				
I/O Ports	1 x Micro USB (DisplayLink input for touch, video and power)				
Video	Input Video Horizontal Sync frequency range: 31.5KHz / Input Video Vertical Sync (frame rate) frequency range: 60Hz				
Power	Input connector: Micro USB Input signal specifications: 5 V ±5% Power Consumption (Typical) - ON: 3.7 W; SLEEP: 0.9 W; OFF: 1.9 W				
Dimensions (H x W x D)	4.61" x 7.11" x 0.7" / 117.22 mm x 180.58 mm x 17.7 mm				
Shipping Dimensions	6.69" x 9.13" x 3.74" / 170 mm x 232 mm x 95 mm				
Weight	Unpackaged - 0.77 lbs / 0.35 kg; Packaged - 1.43 lbs / 0.65 kg				
Mounting Options	VESA 75mm x 75mm				
Temperature	Operating: 0°C to 40°C / 32°F to 104°F; Storage: -20°C to 60°C / -4°F to 140°				
Humidity (non-condensing)	Operating: 20% - 80% / Storage: 10% - 95%				
Regulatory approvals and declarations	approvals and declarations Canada cUL, IC; China CCC; Europe CE; Korea KCC; United States FCC, UL; Japan VCCI; Internationa CB; Australia RCM; Mexico NOM				
Ingress Protection	IP54 and IP65				
Warranty	3 years				
Extended Warranty Options	E898247 - Touchmonitor 4YR Warranty Coverage E898449 - Touchmonitor 5YR Warranty Coverage E898648 - Touchmonitor 3YR Warranty Coverage + AUR E894921 - Touchmonitor 4YR Warranty Coverage + AUR E895125 - Touchmonitor 5YR Warranty Coverage + AUR				
Box Content	Touchmonitor, Micro USB Y-cable, Quick Install Guide				

## **Ordering Information**

Part Number	Part Description	Technology	Surface Treatment	Touch Interface	Color	Mount
E796382	ET0702L-2UWA-1-BL-G	TouchPro PCAP	Anti-glare	USB	Black	Without Stand

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America Tel +1 408 597 8000 Fax +1 408 597 8050

elosales.na@elotouch.com

**Europe**Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
EMEA.Sales@elotouch.com

**Asia-Pacific**Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America Tel +52 55 2281-6958 elosales.latam@elotouch.com



