

EloPOSTM Terminal

Modern. Modular. Made for Retail.



EloPOS Overview

The versatile EloPOS System combines modern aesthetics, modular flexibility and commercial-grade reliability. Purpose-built for point of sale, EloPOS offers a 15.6-inch touchscreen display, choice of Intel's 8th generation processors and an integrated expansion hub to connect the peripherals you need - whether a customer-facing display, payment device, printer, cash drawer, barcode scanner or scale. From traditional POS to self-service applications, EloPOS delivers the durability needed to survive continuous public use and is backed by Elo's standard 3-year warranty.



Retail



Hospitality



Entertainment



Restaurant



Grocery



Connections. Connections. Connections.

The expansion hub allows you to connect all of the POS peripheral support you need. From cash drawers and printers to barcode scanners and payment devices – there is connectivity to cover it all. With two models, the hub is integrated into the base of the EloPOS stand or mounted to the back of the display for pole and wall mount configurations.

Retail Ready

With a retail-hardened design and endless connections for accessories, the EloPOS System is well suited for use in any retail or hospitality environment.



Elo Edge Connect™

You can seamlessly attach any combination of up to four peripherals to the edge of the touchscreen.



Touch ready

Elo's leading TouchPro® PCAP technology



Connectivity

The EloPOS hub offers a variety of ports to meet all application uses.



Customer-facing Display

Easily connect a customer-facing display via USB-C - providing touch, data and power with just one cable.



Seamless Design

Edge-to-edge glass design



Flexible mounting

Use a standard VESA mounting system or optional pole and self-service stands to create the solution you want.

Elo Edge Connect Lets You do More!

Built with versatility in mind, Elo Edge Connect offers a wide assortment of peripheral options. From fixed-lane point of sale to self order solutions, seamlessly attach any combination of up to four peripherals to the edge of the touchscreen creating a bespoke solution. And, you can add or move them later as your needs change!



Stands & Mounts



EloPOS Product Specifications

Display	15.6" diagonal, active matrix TFT LCD (LED)
Aspect Ratio	16:9 (widescreen)
Active Display Area	13.55" x 7.62" / 344.2 mm x 193.5 mm
Dimensions	With Stand: 15.2" x 14.54" x 8.71" / 386.2 mm x 369.3 mm x 221.2 mm Without Stand: 15.2" x 9.8" x 2.89" / 386.2 mm x 248.9 mm x 73.3 mm
Brightness	LCD panel: 220 nits, TouchPro PCAP: 187 nits
Response Time	10 msec
Viewing Angle	Horizontal: 45°/45° or 90° total / Vertical: 15°/35° or 50° total
Contrast Ratio	400:1
Processor	E2: Intel Celeron J4105, E3: Intel Core i3-8100T, E5: Intel Core i5-8500T
Memory (RAM)	E2: 4GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (up to 8GB) E3: 4GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (up to 32GB) E5: 8GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (up to 32GB)
Storage	128GB M.2 SATA SSD, 72 TBW
I/O Ports	3 x USB 3.0, 2 x USB 2.0, 4 x Micro USB 2.0, 1 USB-C, 1 x 24V Powered USB, 2 x 12V Powered USB, 1 x LAN RJ45 (Gigabit), 2 x RJ45, 12V/24V Cash Drawer Port