



# Elo Edge Connect™ 2D Barcode Scanner

For Self-Service and  
Price-Checker Applications



**Compatible with  
Windows & Android**



**Easy to Install**



**2-Year Warranty**

## Product Overview

Improve self-service and price-checker applications with Elo's 2D Barcode Scanner that easily integrates with a variety of Elo touchscreens. The fast, hands-free device provides rapid and accurate scanning of barcodes including linear barcodes and QR codes. Whether on paper, etched into a product or on a mobile screen, the reader can return quick, reliable results.

Our modular design provides our customers with the building blocks to configure a multitude of solutions - making it easy to deploy a variety of solutions from price checkers and self-checkout to visitor management. Start changing the way your customers and employees interact in-store and at work by deploying a new generation of interactive technologies.

**Easily and securely attached the camera to any side of the display via Elo Edge Connect™ technology**

**Next Gen Price Checkers - Offer price-checking plus in-depth product information, virtual customer service, endless aisle and related item recommendations, wayfinding, BOPIS, loyalty and assisted selling.**

**Simplify contactless entry for employees and guests by enabling barcodes & QR codes to be scanned on badges and personal devices**

## Elo Edge Connect™ 2D Barcode Scanner

Model	E384627	E245047
Color	Black	
Compatibility	I-Series for Android I-Series for Windows EloPOS Touchscreen Monitors - 1002L, 1302L, 1502L, 1902L, 1903LM, 2002L, 2202L, 2203LM, 2402L, 2403LM, 2702L, 2703LM Touchscreen Signage - 3202L, 3203L, 4202L, 4303L, 4602L, 5053L, 5502L, 5503L, 5553L, 6553L	
Barcode Engine	SE4720	SE4107
Supported Terminal Modes	SNAPI, HID, CDC, OPOS / IBM Handheld, IBM Tabletop	
Standard Configuration	SNAPI with Imaging Interface, Presentation Mode	
Resolution	1280 X 800	1280 x 960
Illumination & Aiming	Red LED illumination, Orange LED aimer	White LED illumination, Green LED aimer
Ideal Scan Distance	1.6" - 30.0" / 4.06 cm - 76.2 cm (depends on barcode quality, size and environmental conditions)	1.2" - 19.5" / 3.05 cm - 49.5 cm (depends on barcode quality, size and environmental conditions)
Viewing Angle	Horizontal: 48°, Vertical: 30°	Horizontal: 44.5°, Vertical: 33.5°
Beeper Support	Yes	
Supported Symbologies	1D: All major 1D 2D: PDF417, MicroPDF417, Data Matrix, MaxiCode*, QR Code, Micro QR Code, Aztec, Grid Matrix*, DotCode*, Macro PDF Postal*: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), Mailmark. *Default setting may be disabled.	
Dimensions	4.67" x 1.40" x 0.81" / 118.5 mm x 35.46 mm x 20.60 mm	4.67" x 1.05" x 0.76" / 118.5 mm x 26.6 mm x 19.1 mm
Shipping Dimensions	6.89" x 4.49" x 2.72" / 175 mm x 114 mm x 69 mm	
Weight Unpackaged	0.071 lbs / 0.032 kg	0.049 lbs / 0.022 kg
Weight Packaged	0.291 lbs / 0.132 kg	0.26 lbs / 0.12 kg
Temperature	Operating: 10° C to 40° C (50° F to 104° F) / Storage: 0° C to 50° C (32° F to 122° F)	
Humidity (non-condensing)	Operating: 20% - 80% / Storage: 10% - 90%	
Warranty	2 year standard warranty	
What's in the Box	2D Barcode Scanner 2 Mounting screws QIG	

## Ordering Information

Part Number	Description
E384627	Elo Edge Connect 2D Barcode Scanner (4720-Performance)
E245047	Elo Edge Connect 2D Barcode Scanner (4107-Value)

Learn more about Elo at [EloTouch.com](http://EloTouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and Elo Edge Connect are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2021 Elo Touch Solutions, Inc. All rights reserved. 21084AES00146

