

### SPECIFICATIONS Touchmonitor 2403LM

DOCUMENT: PS600279 REV:G

REV DATE: Feb. 20,2020

Page 1 of 6

Model	2403LM	
Color	Black or White	
Active Area	20.75" x 11.67" / 527.04 x 296.46 mm	
Dimensions with Stand	432.9 (H) x 574.6 (W) x 233 (D) mm max 17.04 (H) x 22.62 (W) x 9.17 (D) in max See dimensional drawings for details	
LCD Technology	Active matrix TFT LCD	
Diagonal Size	23.8" / 604.52 mm	
Number of Touches	10 Touches	
On-Screen Display (OSD)	Accessible through switches along the bottom.  Controls: Menu, Power, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H-position, V- position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults, Audio Select, Power LED ON/OFF, Touch through, Touch Interface, DICOM Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese, Korean, Russian Lockouts: OSD, Power	
Mounting Options	VESA 4-hole 100mm mounting interface on rear of unit See dimensional drawings for details	
Aspect Ratio	16:9	
Native Resolution	1920 x 1080	



# SPECIFICATIONS Touchmonitor 2403LM

DOCUMENT: PS600279 REV:G

REV DATE: Feb. 20,2020

Page 2 of 6

Preset Video Timings	640x480 60Hz
9	640 x 400 70Hz
	720x400 70Hz
	800x500 60Hz
	800x600 56, 60Hz
	1024x768 60Hz
	1280X720 58Hz, 60Hz
	1280x800 60Hz
	1280x1024 60Hz
	1366x768 60Hz, 60Hz RB
	1440x900 60Hz, 60Hz RB
	1680x1050 60Hz, 60Hz RB
	1920x1080 50 60Hz
Number of Colors	16.7M
Brightness (typical)	Panel: 250 nits
	With PCAP: 225 nits
Response Time (Tr + Tf) (typical)	16 ms
Viewing Angle (typical)	Horizontal: 89°/89° or 178° total
	Vertical: 89°/89° or 178° total
Contrast Ratio (typical)	1000:1
Video	VGA (VGA DE-15 (DB-15) Male connecter cable included)
	HDMI (HDMI cable included)
	Input Video Horizontal Sync frequency range: 30 – 82KHz
	Input Video Vertical Sync (frame rate) frequency range:50 - 75Hz



# SPECIFICATIONS Touchmonitor 2403LM

DOCUMENT: PS600279 REV:G

REV DATE: Feb. 20,2020

Page 3 of 6

Power	Monitor input power connector: Coaxial power jack (2.1 mm pin outer diameter, 6.4mm barrel inner diameter)
	Monitor input power signal specifications: 12VDC +/- 5%
	Adapter input voltage range: 100-240VAC, 50/60Hz
	Power Consumption:
	Monitor + AC/DC adapter
	ON (Default - 75% Brightness): 15.68 W
	ON (Typical - 100% Brightness): 17.33 W
	SLEEP: 1.09 W
	OFF: 0.24 W
Speakers	2 x 2W internal speakers
I/O Ports	1 x VGA (RS232 touch supported via E810917)
	1 x HDMI
	1 x Combo Jack
	1 x DC jack
	1 x USB Type B
	1 x USB 2.0 Type A
	4 x Micro USB
Peripheral Ports	4 x Micro USB side ports (Top, Bottom, Left, Right)
Weight	Unpackaged with Stand: 21.58lbs / 9.80kg
	Monitor without Stand: 14.73lbs / 6.69kg
	Packaged: 28.45lbs / 12 .92kg
Shipping Dimensions	526 (H) x 680 (W) x 318 (D) mm max
	20.71 (H) x 26.77 (W) x 12.52 (D) in max
Temperature	Operating: 0° C to 40° C / 32°F to 104°F
-	Storage: -20° C to 60° C / -4°F to 140°F
Humidity (non-condensing)	Operating: 20% - 80% Storage: 10% - 95% (38.7 Deg maximum wet bulb temperature)



## SPECIFICATIONS Touchmonitor 2403LM

DOCUMENT: PS600279 REV:G

REV DATE: Feb. 20,2020

Page 4 of 6

Regulatory approvals and declarations	Canada CUL, IC China CCC Europe CE Korea KCC Taiwan BSMI United States FCC, UL Japan VCCI International CB Australia RCM Russia EAC Mexico CoC RoHS, China RoHS, WEEE, REACH India BIS
Healthcare Safety Standards	UL: AAMI /ANSI ES60601-1:2005/(R)2012 and A1:2012, C1:2009/(R)2012 and A2:2010/(R)2012/IEC 60601-1 Ed. 3.1 cUL: (CAN/CSA-C22.2 NO. 60601-1:14 /IEC60601-1 Ed. 3.1 CB: IEC 60601-1:2005+A1:2012 (Ed. 3.1) CE: IEC 60601-1-2:2014 (Ed. 4) Risk Management: ISO 14971:2007 + EN ISO 14971:2012 Usability: IEC 60601-1-6:2010+A1:2013 (Ed. 3.1), IEC 62366:2007+A1:2014 (Ed. 1.1)
DICOM	DICOM Part 14 (AAPM secondary display)
Ingress Protection	IP54 entire enclosure
Impact Protection	IK06
Warranty	3 years 4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated



# SPECIFICATIONS Touchmonitor 2403LM

DOCUMENT: PS600279 REV:G

REV DATE: Feb. 20,2020

Page 5 of 6

What's in the Box	1 x Touchmonitor
	1 x Quick Install Guide
	3 x Tie wraps
	1 x VGA cable
	1 x HDMI cable
	1 x Touch USB cable
	1 x Audio cable
	1 x Power brick (E323104)
	1 x NA Power cable
	1 x EU Power cable
	1 x EEI Label
	1 x DICOM calibration sheet

Part Number	Part Description	Touch Technology	Surface Treatment	Touch Interface	Color
E659195	ET2403LM-2UWB-1-BL-G	TouchPro PCAP	AG	USB, Serial (via VGA)	Black
E659395	ET2403LM-2UWB-1-WH-G	TouchPro PCAP	AG	USB, Serial (via VGA)	White

Document Number	Description
MS601975	Dimensional drawings
MD600080	Regulatory certificates
UM600504	User Guide – REVB, English
UM600505	User Guide – REVB, French
UM600506	User Guide – REVB, Italian
UM600507	User Guide – REVB, German
UM600508	User Guide – REVB, Spanish
UM600509	User Guide – REVB, Russian



## SPECIFICATIONS Touchmonitor 2403LM

DOCUMENT: PS600279 REV:G

REV DATE: Feb. 20,2020

Page 6 of 6

UM600510	User Guide – REVB, Japanese	
UM600511	User Guide – REVB, Simplified Chinese	
UM600512	User Guide – REVB, Traditional Chinese	
UM600513	User Guide – REVB, Korean	

MTBF (Mean Time Between Failures) An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit's reliability; thus MTBF is not, and should not be construed as, a warranty measurement.

	Part #
0.41. 45.11.14.1	(RoHS
Options/Peripheral/Upgrades	Compliant)
Magnetic Stripe Reader - Black	E001002
Magnetic Stripe Reader - White	E352392
Privacy Screen 24-in	E352977
Elo Stand 2402/3-2702/3 - Black	E509844
Elo Stand 2402/3-2702/3 – White	E510042
Elo Monitor Handles – 1 Set	E352196
Wall mount	E143088
North America Power Cable – C13	E593865
Australia Power Cable – C13	E594067
Europe Power Cable – C13	E594264
Korea Power Cable – C13	E594466
China Power Cable – C13	E594670
Taiwan Power Cable – C13	E594869
Japan Power Cable – C13	E793799
Power Brick – 65W	E593253
Shelf mount	E043382
Pole Mount Bracket	E045151
Pcap Stylus	E066148
ELO-KIT-19-27 02/03 Series Cables 1.8m-R	E408193
ELO-KIT-YCABLE-IDS (Serial Touch & VGA Video Y-Cable)	E810917