

Aspect Ratio

Native Resolution

SPECIFICATIONS Touchmonitor 2703LM

DOCUMENT: PS600280 REV: F REV DATE: Feb. 24, 2020 Page 1 of 6

Model	2703LM	
Color	Black or White	
Active Area	23.54" x 13.24" / 597.88 x 336.31 mm	
Dimensions with Stand	450.9 (H) x 647.6 (W) x 233 (D) mm max 17.75 (H) x 25.50 (W) x 9.17 (D) in max See dimensional drawings for details	
LCD Technology	Active matrix TFT LCD	
Diagonal Size	27" / 685.8 mm	
Number of Touches	10 Touches	
On-Screen Display (OSD)	Accessible through switches along the bottom.	
	Controls: Menu, Power, Up, Down, Select Settings: Brightness, Contrast, Clock, Phase, H-position, V- position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, Volume, Mute, Recall Defaults, Audio Select, Power LED ON/OFF, Touch through, Touch Interface, DICOM	
	Languages : English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese, Korean, Russian	
	Lockouts: OSD, Power	
Mounting Options	VESA 4-hole 100mm mounting interface on rear of unit	

See dimensional drawings for details

16:9

1920 x 1080



SPECIFICATIONS Touchmonitor 2703LM

DOCUMENT: PS600280 REV: F REV DATE: Feb. 24, 2020 Page 2 of 6

d)
,
lz
0 - 75Hz
1



SPECIFICATIONS Touchmonitor 2703LM

DOCUMENT: PS600280 REV: F REV DATE: Feb. 24, 2020 Page 3 of 6

Power	Monitor input power connector: Coaxial power jack (2.1 mm pir outer diameter, 6.4mm barrel inner diameter) Monitor input power signal specifications: 12VDC +/- 5% Adapter input voltage range: 100-240VAC, 50/60Hz	
	Power Consumption:	
	Monitor + AC/DC adapter	
	ON (Default - 75% Brightness): 17.37 W	
	ON (Typical - 100% Brightness): 22.41W	
	SLEEP: 1.006 W	
	OFF: 0.24 W	
Speakers	2 x 2W internal speakers	
I/O Ports	1 x VGA (RS232 touch supported via E810917)	
	1 x HDMI	
	1 x Combo Jack	
	1 x DC jack	
	1 x USB Type B	
	1 x USB 2.0 Type A	
	4 x Micro USB	
Peripheral Ports	4 x Micro USB side ports (Top, Bottom, Left, Right)	
Weight	Unpackaged with Stand: 22.64 lbs /10.27 kg	
	Monitor without Stand: 15.72 lbs / 7.13 kg	
	Packaged: 31.48lbs / 14.28kg	
Shipping Dimensions	560 (H) x 764 (W) x 322 (D) mm max	
	22.05 (H) x 30.08 (W) x 12.68 (D) in max	
Temperature	Operating: 0° C to 40° C / 32°F to 104°F Storage: -20° C to 60° C / -4°F to 140°F	
Humidity (non-condensing)	Operating: 20% - 80% Storage: 10% - 95% (38.7 Deg maximum wet bulb temperature)	



SPECIFICATIONS Touchmonitor 2703LM

DOCUMENT: PS600280 REV: F REV DATE: Feb. 24, 2020 Page 4 of 6

Regulatory approvals and declarations	Canada CUL, IC China CCC Europe CE Korea KCC Taiwan BSMI United States FCC, UL Japan VCCI International CB Australia RCM Russia EAC Mexico CoC RoHS, China RoHS, WEEE, REACH India BIS
Healthcare Safety Standards	UL: AAMI /ANSI ES60601-1:2005/(R)2012 and A1:2012, C1:2009/(R)2012 and A2:2010/(R)2012/IEC 60601-1 Ed. 3.1 cUL: (CAN/CSA-C22.2 NO. 60601-1:14 /IEC60601-1 Ed. 3.1 CB: IEC 60601-1:2005+A1:2012 (Ed. 3.1) CE: IEC 60601-1-2:2014 (Ed. 4) Risk Management: ISO 14971:2007 + EN ISO 14971:2012 Usability: IEC 60601-1-6:2010+A1:2013 (Ed. 3.1), IEC 62366:2007+A1:2014 (Ed. 1.1)
DICOM	DICOM Part 14 (AAPM secondary display)
Ingress Protection	IP54 entire enclosure
Impact Protection	IK06
Warranty	3 years 4 year warranty coverage - Elo P/N: E898247 5 year warranty coverage - Elo P/N: E898449 3 year warranty coverage + AUR - Elo P/N: E898648 4 year warranty coverage + AUR - Elo P/N: E894921 5 year warranty coverage + AUR - Elo P/N: E895125
MTBF	50,000 hours demonstrated



SPECIFICATIONS Touchmonitor 2703LM

DOCUMENT: PS600280 REV: F REV DATE: Feb. 24, 2020 Page 5 of 6

What's in the Box	1 x Touchmonitor
	1 x Quick Install Guide
	3 x Tie wraps
	1 x VGA cable
	1 x HDMI cable
	1 x Touch USB cable
	1 x Audio cable
	1 x Power brick (E323104)
	1 x NA Power cable
	1 x EU Power cable
	1 x EEI Label
	1 x DICOM calibration sheet

Part Number	Part Description	Touch Technology	Surface Treatment	Touch Interface	Color
E659596	ET2703LM-2UWB-1-BL-G	TouchPro PCAP	AG	USB, Serial (via VGA)	Black
E659793	ET2703LM-2UWB-1-WH-G	TouchPro PCAP	AG	USB, Serial (via VGA)	White

Document Number	Description
MS601976	Dimensional drawings
MD600080	Regulatory certificates
UM600504	User Guide – REVB, English
UM600505	User Guide – REVB, French
UM600506	User Guide – REVB, Italian
UM600507	User Guide – REVB, German
UM600508	User Guide – REVB, Spanish
UM600509	User Guide – REVB, Russian
UM600510	User Guide – REVB, Japanese



SPECIFICATIONS Touchmonitor 2703LM

DOCUMENT: PS600280 REV: F REV DATE: Feb. 24, 2020

REV DATE: Feb. 24, 2020 Page 6 of 6

UM600511	User Guide – REVB, Simplified Chinese
UM600512	User Guide – REVB, Traditional Chinese
UM600513	User Guide – REVB, Korean

MTBF (Mean Time Between Failures) An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit's reliability; thus MTBF is not, and should not be construed as, a warranty measurement.

	Part #
0 (1 (0) 1 (1)	(RoHS
Options/Peripheral/Upgrades	Compliant)
Magnetic Stripe Reader - Black	E001002
Magnetic Stripe Reader - White	E352392
Privacy Screen 27-in	E353170
Elo Stand 2402/3-2702/3 - Black	E509844
Elo Stand 2402/3-2702/3 – White	E510042
Elo Monitor Handles – 1 Set	E352196
Wall mount	E143088
North America Power Cable – C13	E593865
Australia Power Cable – C13	E594067
Europe Power Cable – C13	E594264
Korea Power Cable – C13	E594466
China Power Cable – C13	E594670
Taiwan Power Cable – C13	E594869
Japan Power Cable – C13	E793799
Power Brick – 65W	E593253
Shelf mount	E043382
Pole Mount Bracket	E045151
Pcap Stylus	E066148
ELO-KIT-19-27 02/03 Series Cables 1.8m-R	E408193
ELO-KIT-YCABLE-IDS (Serial Touch & VGA Video Y-Cable)	E810917