



Elo Touch Solutions, Inc.  
 670 N. McCarthy Blvd., Suite 100  
 Milpitas, CA 95035  
 www.elotouch.com

**SPECIFICATIONS**  
**Touchcomputer**  
**EloPOS Rev A**

DOCUMENT: PS600353  
 REV: G  
 REV DATE: July 28, 2020  
 Page 0 of 8

**TITLE: PRODUCT SPECIFICATIONS, EloPOS REV A**

**NUMBER:**

**REVISION: G**

**OWNER: Engineering**

Change History			
Rev	Author	Date	Description
1	Chunying Huang	Nov 2, 2018	- Initial draft
2	Chunying Huang	Dec 12, 2018	- Add dimensions, weight and power consumption info
3	Chunying Huang	Dec 28, 2018	- Add optionals stand, mount kits
4	Chunying Huang	Jan 7, 2019	- Update SKU description - Add Elo warranty P/N's - Update wording Z-Series to EloPOS
5	Chunying Huang	March 13, 2019	- Remove NFC/RFID kit
A	Chunying Huang	April 3, 2019	- Initial release CO-19-0604
B	Chunying Huang	June 4, 2019	Revise per CO-19-1015 - Correct storage form factor from 2.5" to M.2 - Update warranty coverage part numbers
C	Chunying Huang	June 18, 2019	Revise per CO-19-1372 - Add Brazil ANATEL certificate - Update required mount kit for 1002 and 1302 customer facing display - Update USB-C cable description to make it more clear - Add 6ft USB-C cable P/N for 1302
D	Chunying Huang	Jan. 16, 2020	Revise per CO-20-0186 - Update upgrade option list - Remove optional product coverage section - Remove Dallas Key kit - Add 15.6" FHD, 21.5" FHD and 15" 4:3 SKUs
E	Chunying Huang	03/23/2020	Revise per CO-20-0446



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchcomputer

### EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 1 of 8

			<ul style="list-style-type: none"><li>- Update description for supported OS list</li><li>- Update optional memory and SSD kit P/N's</li></ul>
F	Chunying Huang	5/15/2020	<ul style="list-style-type: none"><li>Revise per CO-20-0746</li><li>- Add status light kit support</li></ul>
G	Chunying Huang	6/29/2020	<ul style="list-style-type: none"><li>Revise per CO-20-</li><li>- Add new EloPOS SKUs</li><li>- Update 10" 2<sup>nd</sup> display monitor to Type-C models</li><li>- Add new storage options</li></ul>



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

## SPECIFICATIONS

### Touchcomputer EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 2 of 8

Model	Celeron Model	i3 Model	i5 Model	
Enclosure Color	Black			
Active Display Area (W x H)	15.6" 16:9 SKUs: 13.55" x 7.62" (344.2mm x 193.5mm) 21.5" 16:9 SKUs: 18.74" x 10.54" (476.1mm x 267.8mm) 15" 4:3 SKUs: 11.97" x 8.98" (304.1mm x 228.1mm)			
Maximum Touchcomputer Dimensions With Stand (W x H x D)	15.6" 16:9 SKUs: 15.2" x 14.54" x 8.71" (386.2mm x 369.3mm x 221.2mm) 21.5" 16:9 SKUs: 16.4" x 20.7" x 10.15" (416.4 mm x 525.9mm x 257.8mm) 15" 4:3 SKUs: 14.16" x 15.37" x 8.71" (359.7mm x 390.4mm x 221.3mm)			
Maximum Touchcomputer Dimensions Without Stand (W x H x D)	15.6" 16:9 SKUs: 15.2" x 9.8" x 2.89" (386.2mm x 248.9mm x 73.3mm) 21.5" 16:9 SKUs: 16.4" x 20.7" x 3.33" (416.4 mm x 525.9mm x 84.7mm) 15" 4:3 SKUs: 14.16" x 11.17" x 3.07" (359.7mm x 283.7mm x 78.1mm)			
LCD Technology	Active matrix TFT LED LCD			
Diagonal Size	15.6" 16:9 SKUs: 15.55" (395mm) diagonal 21.5" 16:9 SKUs: 21.5" (546.1mm) diagonal 15" 4:3 SKUs: 15.0" (381mm) diagonal			
Processor	Intel® Celeron® Processor J4105 (4M Cache, up to 2.5 GHz)	Intel® Core™ i3-8100T Processor (6M Smart Cache, 3.10 GHz)	Intel® Core™ i5-8500T Processor (9M Smart Cache, up to 3.50 GHz by Intel® Turbo Boost Technology 2.0) Intel® vPro Support	
Chipset	N/A	Intel H310 Express	Intel Q370 Express	
Video	Intel UHD Graphics 600	Intel UHD Graphics 630		
BIOS	AMI			
Memory (RAM)	4GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (Expandable to 8GB maximum <sup>1</sup> on 2 slots) <sup>3</sup>	4GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (Expandable to 32GB maximum <sup>2</sup> on 2 slots) <sup>3</sup>	8GB 2400MHz DDR4 SO-DIMM on 1 of 2 slots (Expandable to 32GB maximum <sup>2</sup> on 2 slots) <sup>3</sup>	
	<sup>1</sup> Maximum memory using 2 slots. Expandable up to 8GB maximum, SO-DIMM DDR4-2400. <sup>3</sup> Check brand of the memory included in your unit before purchasing the memory kit.	<sup>2</sup> Maximum memory using 2 slots. Expandable up to 32GB maximum, SO-DIMM DDR4-2400. <sup>3</sup> Check brand of the memory included in your unit before purchasing the memory kit.		



Elo Touch Solutions, Inc.  
 670 N. McCarthy Blvd., Suite 100  
 Milpitas, CA 95035  
 www.elotouch.com

## SPECIFICATIONS

### Touchcomputer EloPOS Rev A

DOCUMENT: PS600353  
 REV: G  
 REV DATE: July 28, 2020  
 Page 3 of 8

Storage	128GB M.2 SATA SSD <sup>4</sup> : <b>80 TBW</b> <b>256GB M.2 SATA SSD<sup>4</sup>: 160 TBW</b> Optional M.2 PCIe (NVMe) SSD for selected SKUs <small><sup>4</sup>GB equals one billion bytes when referring to storage capacity. Accessible capacity may be less.</small>	
Mounting Options	15.6" 16:9 SKUs: 75mm VESA mount 21.5" 16:9 SKUs: 75mm or 100mm VESA mount 15" 4:3 SKUs: 15.0" 75mm VESA mount	
Ethernet Port	1 x LAN RJ45 (Gigabit)	
Wireless LAN	802.11 a/b/g/n/ac 2.4GHz and 5GHz	
Bluetooth	BT 5.0	
USB Ports	3 x USB 3.0 ( 1 on display head, 2 on I/O) 2 x USB 2.0 on I/O 4 x Micro USB 2.0 on edges for optional Elo peripherals.	
RAID	N/A	
TPM	TPM 2.0	
AMT	N/A	Active Management Technology (Intel® AMT 11.0) Support.
Powered USB	1 x 24V on I/O 2 x 12V on I/O	
Serial Ports	2 x RJ45	
Cash Drawer Port	12V/24V Cash Drawer Port on I/O (EPSON Pinout, 24V default; selectable by internal switch)	
Additional Video Out	1 x Full-function USB-C (Power up to 27W, USB 3.0, Display Port)	
Audio Ports	1 x 3.5 mm headset jack	
Speakers	Two 2W internal speakers	
Operating System Options	No Operating System Microsoft Windows 10 IoT Enterprise LTSC 64-bit Optional - Microsoft Windows 10 Professional English 64-bit	
Languages	Windows 10 - 36 Language groups	
Native (optimal) Resolution	15.6" 16:9 SKUs: 1366 x 768 @ 60Hz or 1920 x 1080 @ 60Hz 21.5" 16:9 SKUs: 1920 x 1080 @ 60Hz 15" 4:3 SKUs: 1024 x 768 @ 60Hz	
Control Buttons	Power Button	
Aspect Ratio	15.6" 16:9 SKUs: 16:9 (standard) 21.5" 16:9 SKUs: 16:9 (standard) 15" 4:3 SKUs: 4:3 (standard)	
Number of Colors	15.6" 16:9 SKUs: 262,144 21.5" 16:9 SKUs: 16,7M 15" 4:3 SKUs: 262,144	



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

## SPECIFICATIONS

### Touchcomputer EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 4 of 8

Brightness (typical)	<p>15.6" 16:9 HD SKUs: LCD panel: 220 nits TouchPro PCAP: 187 nits</p> <p>15.6" 16:9 Full HD SKUs: LCD panel: 300 nits TouchPro PCAP: 255 nits</p> <p>21.5" 16:9 SKUs: LCD panel: 250 nits TouchPro PCAP: 212.5 nits</p> <p>15" 4:3 SKUs: LCD panel: 400 nits TouchPro PCAP: 340 nits</p>
Response Time Total (typical)	<p>15.6" E SKUs: 10 msec 15.6" 16:9 Full HD SKUs: 25 msec 21.5" 16:9 SKUs: 14 msec 15" 4:3 SKUs: 23 msec</p>
Viewing Angle (typical)	<p>15.6" E SKUs: Horizontal: 45°/45° or 90° total / Vertical: 15°/35° or 50° total</p> <p>15.6" 16:9 Full HD SKUs: Horizontal: 80°/80° or 160° total / Vertical: 80°/80° or 160° total</p> <p>21.5" 16:9 SKUs: Horizontal: 89°/89° or 178° total / Vertical: 89°/89° or 178° total</p> <p>15" 4:3 SKUs: Horizontal: 80°/80° or 160° total / Vertical: 80°/80° or 160° total</p>
Contrast Ratio (typical)	<p>15.6" E SKUs: 400:1 15.6" 16:9 Full HD SKUs: 700:1 21.5" 16:9 SKUs: 1000:1 15" 4:3 SKUs: 800:1</p>
Power Supply	<p>External 24VDC universal-type power supply brick AC input voltage: 100-240 VAC Input frequency: 50-60 Hz Maximum output power: 180W</p>
Max Power Consumption (without peripherals)	<p>15.6" 16:9 HD SKUs - E2: 24W, E3: 65W, E5: 74W 15.6" 16:9 Full HD SKUs - H2: 26W, 15.6" H3: 67W, 15.6" H5: 76W 21.5" 16:9 SKUs - H2: 31W, 21.5" H3: 72W, 21.5" H5: 81W 15" 4:3 SKUs - S2: 30W, 15" S3: 71W, 15" S5: 80W</p>
Energy Star Certified	Energy Star 7.1



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

## SPECIFICATIONS

### Touchcomputer

### EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 5 of 8

Shipping Box Dimensions (W x H x D)	<p>15.6" 16:9 SKUs: With Stand: 18.19" x 11.77" x 18.5" / 462mm x 299mm x 470mm Without Stand: 18.19" x 8.5" x 13.57" / 462mm x 216mm x 346mm</p> <p>21.5" 16:9 SKUs: With Stand: 25.35" x 14.76" x 21.57" / 644mm x 375mm x 548mm Without Stand: 25.35" x 8.9" x 17.72" / 644mm x 226mm x 450mm</p> <p>15" 4:3 SKUs: With Stand: 17.91" x 14.65" x 20.04" / 455mm x 372mm x 509mm <b>Without Stand: 18.19" x 8.50" x 14.80" / 462mm x 216mm x 376mm</b></p>
Weight	<p>15.6" 16:9 SKUs: With Stand: 10.8 lbs / 4.9 kg Without Stand: 6.4 lbs / 2.9 kg</p> <p>21.5" 16:9 SKUs: With Stand: 19.6 lbs / 8.9 kg Without Stand: 13.2 lbs / 6 kg</p> <p>15" 4:3 SKUs: With Stand: 11.6 lbs / 5.3 kg <b>Without Stand: 7.61lbs / 3.45kg</b></p>
Shipping Weight	<p>15.6" 16:9 Full HD SKUs: With Stand: 16.1 lbs / 7.3 kg Without Stand: 10.8 lbs / 4.9 kg</p> <p>21.5" 16:9 SKUs: With Stand: 26.2 lbs / 11.9 kg Without Stand: 18.5 lbs / 8.4 kg</p> <p>15" 4:3 SKUs: With Stand: 18.1 lbs / 8.2 kg <b>Without Stand: 11.02 lbs / 5kg</b></p>
Temperature	<p>Operating: 0°C to 35°C (32°F to 95°F) Storage: -20°C to 60°C (-4°F to 140°F)</p>
Humidity (non-condensing)	<p>Operating: 20% to 80% Storage: 5% to 95% (38.7°C max wet bulb temperature)</p>
Regulatory approvals and declarations	UL/cUL , FCC, TUV, CE, CB, Mexico NOM, C-Tick/RCM, VCCI, Argentina S-Mark, CCC
Form Factor	Desktop
Real-Time Clock	Replaceable CR2032 lithium metal battery for clock
MTBF	50,000 hours demonstrated
Sealability	<p>Touchscreen sealed to sub-bezel Touchscreen sealed to LCD</p>
Power Cables	North American and European power cables included



Elo Touch Solutions, Inc.  
 670 N. McCarthy Blvd., Suite 100  
 Milpitas, CA 95035  
 www.elotouch.com

## SPECIFICATIONS

### Touchcomputer EloPOS Rev A

DOCUMENT: PS600353  
 REV: G  
 REV DATE: July 28, 2020  
 Page 6 of 8

Other Features	<p>Serviceable internal components.</p> <p>Models with a stand for desktop application.</p> <p>Models without a stand for 75mm VESA mounting.</p> <p>Models without a stand for 75mm or 100mm VESA mounting (21.5" models only).</p> <p>Kensington lock.</p>
Upgrade Options	<p>4GB 2666 MHz DDR4 Memory SO-DIMM – Elo P/N: E264186</p> <p>8GB 2666 MHz DDR4 Memory SO-DIMM – Elo P/N: E264375</p> <p>16GB 2666 MHz DDR4 Memory SO-DIMM – Elo P/N: E263989</p> <p>M.2 SATA 128GB SSD – Elo P/N: E206352</p> <p>M.2 SATA 256GB SSD – Elo P/N: E206556</p>
Accessories	
Stand, Mounts & Kits	<ul style="list-style-type: none"> <li>- EloPOS Rear Facing Display Mount Kit – Elo P/N: E835969 (Kit includes authorized E969524 Elo 2ft USB-C cable)</li> <li>- Shelf Mount Bracket – Elo P/N: E043382</li> <li>- Floor Stand for 10/15/22" I-Series – Elo P/N: E048069</li> <li>- Pole Mount – 6 inch – Elo P/N: E047458</li> <li>- Pole Mount – 12 inch – Elo P/N: E047663</li> <li>- Pole Mount – 18 inch – Elo P/N: E047864</li> <li>- Pole Mount Bracket – Elo P/N: E045151</li> </ul>
Optional Peripherals	<ul style="list-style-type: none"> <li>- Biometric Fingerprint Reader (FPR) – Elo P/N: E001001</li> <li>- Magnetic Stripe Reader (MSR) – Elo P/N: E001002</li> <li>- Customer Display (2x20 VFD) – Elo P/N: E001003</li> <li>- 2D Barcode Reader (BCR) – Elo P/N: E926356</li> <li>- 10" LCD customer display (10 touch) – <b>Elo P/N E155834</b> (requires display mount kit E835969)</li> <li>- 10" LCD customer display (no touch) – <b>Elo P/N E324341</b> (requires display mount kit E835969)</li> <li>- ET1302L-2UWA-1-BL-NS-G – Elo P/N: E683595 (requires display mount kit E835969 which includes authorized Elo 2ft USB-C cable)</li> <li>- EMV Cradle for eDynamo – Elo P/N: E375343</li> <li>- EMV Cradle for Ingenico RP457c (with BT and USB) – Elo P/N: E710930</li> <li>- EMV Cradle for Ingenico RP457c (with Audio Jack, BT and USB) - Elo P/N: E586981</li> <li>- 6ft Elo authorized USB-C cable – Elo P/N: E710364</li> <li>- Elo Status Light Kit – Elo P/N: E466847</li> </ul> <p><b>(System serial number needs to be C203033531 or later to be supported on Intel Celeron models; System serial number needs to be C203026849 or later to be supported on Intel i3/i5 models)</b></p> <p><b>Important: All current EPSxxEx SKUs do not support status light kit.</b></p>



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchcomputer

### EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 7 of 8

Warranty	Three years (Extend two years with additional charge)  4 year warranty coverage - Elo P/N: E819598 5 year warranty coverage - Elo P/N: E819795 3 year warranty coverage + AUR - Elo P/N: E820186 4 year warranty coverage + AUR - Elo P/N: E820388 5 year warranty coverage + AUR - Elo P/N: E820582
What's in the box	<ul style="list-style-type: none"><li>- EloPOS Touchcomputer</li><li>- North America Power Cord</li><li>- EU Power Cord</li><li>- Power Adapter – 180W</li><li>- Cable RJ-45 to DB-9</li><li>- Cable cover locking screw</li><li>- Quick Installation Guide (QIG)</li></ul>





Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

## SPECIFICATIONS

### Touchcomputer EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 8 of 8

#### Part Number(s) for EloPOS 15.6-inch HD AiO Touchscreen Computer

Part Number	Part Description	Processor	OS	Memory	Storage	Touch Interface
E440439	EPS15E2-2UWA-1-MT-4G-1S-NO-00-BK	J4105	None	4GB	128GB SSD	USB
E440234	EPS15E2-2UWA-1-MT-4G-1S-W1-64-BK	J4105	Window 10	4GB	128GB SSD	USB
E441010	EPS15E2-2UWA-1-MT-4G-1S-NO-00-BK-NS-EXP	J4105	None	4GB	128GB SSD	USB
E440808	EPS15E2-2UWA-1-MT-4G-1S-W1-64-BK-NS-EXP	J4105	Window 10	4GB	128GB SSD	USB
E441385	EPS15E3-2UWA-1-MT-4G-1S-NO-00-BK	i3-8100T	None	4GB	128GB SSD	USB
E441193	EPS15E3-2UWA-1-MT-4G-1S-W1-64-BK	i3-8100T	Window 10	4GB	128GB SSD	USB
E441781	EPS15E3-2UWA-1-MT-4G-1S-NO-00-BK-NS-EXP	i3-8100T	None	4GB	128GB SSD	USB
E441575	EPS15E3-2UWA-1-MT-4G-1S-W1-64-BK-NS-EXP	i3-8100T	Window 10	4GB	128GB SSD	USB
<b>E262258</b>	<b>EPS15E3-2UWA-1-MT-8G-1S-W1-64-BK</b>	<b>i3-8100T</b>	<b>Window 10</b>	<b>8GB</b>	<b>128GB SSD</b>	<b>USB</b>
<b>E263402</b>	<b>EPS15E3-2UWA-1-MT-8G-1S-NO-00-BK-NS-EXP</b>	<b>i3-8100T</b>	<b>None</b>	<b>8GB</b>	<b>128GB SSD</b>	<b>USB</b>
E442161	EPS15E5-2UWA-1-MT-8G-1S-NO-00-BK	i5-8500T	None	8GB	128GB SSD	USB
E441968	EPS15E5-2UWA-1-MT-8G-1S-W1-64-BK	i5-8500T	Window 10	8GB	128GB SSD	USB
E442550	EPS15E5-2UWA-1-MT-8G-1S-NO-00-BK-NS-EXP	i5-8500T	None	8GB	128GB SSD	USB
E442365	EPS15E5-2UWA-1-MT-8G-1S-W1-64-BK-NS-EXP	i5-8500T	Window 10	8GB	128GB SSD	USB
<b>E892954</b>	<b>EPS15E5-2UWA-1-MT-8G-2S-W1-64-BK-NS-EXP</b>	<b>i5-8500T</b>	<b>Window 10</b>	<b>8GB</b>	<b>256GB SSD</b>	<b>USB</b>
<b>E877703</b>	<b>EPS15E5-2UWA-1-MT-6G-1S-W1-64-BK</b>	<b>i5-8500T</b>	<b>Window 10</b>	<b>16GB</b>	<b>128GB SSD</b>	<b>USB</b>
<b>E892761</b>	<b>EPS15E5-2UWA-1-MT-8G-2S-W1-64-BK</b>	<b>i5-8500T</b>	<b>Window 10</b>	<b>8GB</b>	<b>256GB SSD</b>	<b>USB</b>

#### Part Number(s) for EloPOS 15.6-inch FHD AiO Touchscreen Computer

Part Number	Part Description	Processor	OS	Memory	Surface Treatment	Touch Interface
E935572	EPS15H2-2UWA-1-MT-4G-1S-NO-00-BK	J4105	None	4GB	Antiglare	USB
E935367	EPS15H2-2UWA-1-MT-4G-1S-	J4105	Window 10	4GB	Antiglare	USB



Elo Touch Solutions, Inc.  
 670 N. McCarthy Blvd., Suite 100  
 Milpitas, CA 95035  
 www.elotouch.com

## SPECIFICATIONS

### Touchcomputer EloPOS Rev A

DOCUMENT: PS600353  
 REV: G  
 REV DATE: July 28, 2020  
 Page 9 of 8

	W1-64-BK					
<b>E395937</b>	<b>EPS15H2-2UWA-1-MT-4G-1S- W1-64-BK-NS-EXP</b>	<b>J4105</b>	<b>Window 10</b>	<b>4GB</b>	<b>128GB SSD</b>	<b>USB</b>
E935967	EPS15H3-2UWA-1-MT-4G-1S- NO-00-BK	i3-8100T	None	4GB	128GB SSD	USB
E935775	EPS15H3-2UWA-1-MT-4G-1S- W1-64-BK	i3-8100T	Window 10	4GB	128GB SSD	USB
<b>E407627</b>	<b>EPS15H3-2UWA-1-MT-4G-1S- NO-00-BK-NS-EXP</b>	<b>i3-8100T</b>	<b>None</b>	<b>4GB</b>	<b>128GB SSD</b>	<b>USB</b>
<b>E396134</b>	<b>EPS15H3-2UWA-1-MT-4G-1S- W1-64-BK-NS-EXP</b>	<b>i3-8100T</b>	<b>Window 10</b>	<b>4GB</b>	<b>128GB SSD</b>	<b>USB</b>
E936365	EPS15H5-2UWA-1-MT-8G-1S- NO-00-BK	i5-8500T	None	8GB	128GB SSD	USB
E936163	EPS15H5-2UWA-1-MT-8G-1S- W1-64-BK	i5-8500T	Window 10	8GB	128GB SSD	USB
E936750	EPS15H5-2UWA-1-MT-8G-1S- NO-00-BK-NS-EXP	i5-8500T	None	8GB	128GB SSD	USB
E936556	EPS15H5-2UWA-1-MT-8G-1S- W1-64-BK-NS-EXP	i5-8500T	Window 10	8GB	128GB SSD	USB
E939305	EPS15H5-2UWA-1-MT-6G-2S- W1-64-BK	i5-8500T	Window 10	16GB	256GB SSD	USB
E939498	EPS15H5-2UWA-1-MT-6G-2S- W1-64-BK-NS-EXP	i5-8500T	Window 10	16GB	256GB SSD	USB
<b>E536624</b>	<b>EPS15H5-2UWA-1-MT-8G-2S- W1-64-BK</b>	<b>i5-8500T</b>	<b>Window 10</b>	<b>8GB</b>	<b>256GB SSD</b>	<b>USB</b>

#### Part Number(s) for EloPOS 15-inch 4:3 AiO Touchscreen Computer

Part Number	Part Description	Processor	OS	Memory	Storage	Touch Interface
E931330	EPS15S2-2UWA-1-MT-4G-1S- NO-00-BK	J4105	None	4GB	128GB SSD	USB
E931524	EPS15S2-2UWA-1-MT-4G-1S- W1-64-BK	J4105	Window 10	4GB	128GB SSD	USB
<b>E286726</b>	<b>EPS15S2-2UWA-1-MT-4G-1S- NO-00-WH</b>	<b>J4105</b>	<b>None</b>	<b>4GB</b>	<b>128GB SSD</b>	<b>USB</b>
<b>E263803</b>	<b>EPS15S2-2UWB-1-MT-4G-1S- W1-64-WH</b>	<b>J4105</b>	<b>Window 10</b>	<b>4GB</b>	<b>128GB SSD</b>	<b>USB</b>
<b>E590979</b>	<b>EPS15S2-2UWA-1-MT-4G-1S- NO-00-BK-NS-EXP</b>	<b>J4105</b>	<b>None</b>	<b>4GB</b>	<b>128GB SSD</b>	<b>USB</b>
<b>E494164</b>	<b>EPS15S2-2UWA-1-MT-4G-1S- W1-64-BK-NS-EXP</b>	<b>J4105</b>	<b>Window 10</b>	<b>4GB</b>	<b>128GB SSD</b>	<b>USB</b>
<b>E587032</b>	<b>EPS15S2-2UWA-1-MT-8G-1S- NO-00-BK-NS-EXP</b>	<b>J4105</b>	<b>None</b>	<b>8GB</b>	<b>128GB SSD</b>	<b>USB</b>
E931706	EPS15S3-2UWA-1-MT-4G-1S- NO-00-BK	i3-8100T	None	4GB	128GB SSD	USB



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

## SPECIFICATIONS

### Touchcomputer EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 10 of 8

E931896	EPS15S3-2UWA-1-MT-4G-1S-W1-64-BK	i3-8100T	Window 10	4GB	128GB SSD	USB
E590570	EPS15S3-2UWA-1-MT-4G-1S-NO-00-BK-NS-EXP	i3-8100T	None	4GB	128GB SSD	USB
E494361	EPS15S3-2UWA-1-MT-4G-1S-W1-64-BK-NS-EXP	i3-8100T	Window 10	4GB	128GB SSD	USB
E932090	EPS15S5-2UWA-1-MT-8G-1S-NO-00-BK	i5-8500T	None	8GB	128GB SSD	USB
E932274	EPS15S5-2UWA-1-MT-8G-1S-W1-64-BK	i5-8500T	Window 10	8GB	128GB SSD	USB
E407443	EPS15S5-2UWA-1-MT-8G-1S-W1-64-BK-NS-EXP	i5-8500T	Window 10	8GB	128GB SSD	USB
E485078	EPS15S5-2UWA-1-MT-8G-1S-NO-00-BK-NS-EXP	i5-8500T	None	8GB	128GB SSD	USB
E590763	EPS15S5-2UWA-1-MT-8G-2S-NO-00-BK-NS-EXP	i5-8500T	None	8GB	256GB SSD	USB

#### Part Number(s) for EloPOS 21.5-inch FHD AiO Touchscreen Computer

Part Number	Part Description	Processor	OS	Memory	Storage	Touch Interface
E937154	EPS22H2-2UWA-1-MT-4G-1S-NO-00-BK	J4105	None	4GB	128GB SSD	USB
E936953	EPS22H2-2UWA-1-MT-4G-1S-W1-64-BK	J4105	Window 10	4GB	128GB SSD	USB
E413988	EPS22H2-2UWA-1-MT-4G-1S-NO-00-BK-NS-EXP	J4105	None	4GB	128GB SSD	USB
E414192	EPS22H2-2UWA-1-MT-4G-1S-W1-64-BK-NS-EXP	J4105	Window 10	4GB	128GB SSD	USB
E511988	EPS22H2-2UWA-1-MT-8G-1S-NO-00-BK-NS-EXP	J4105	None	8GB	128GB SSD	USB
E937523	EPS22H3-2UWA-1-MT-4G-1S-NO-00-BK	i3-8100T	None	4GB	128GB SSD	USB
E937340	EPS22H3-2UWA-1-MT-4G-1S-W1-64-BK	i3-8100T	Window 10	4GB	128GB SSD	USB
E410884	EPS22H3-2UWA-1-MT-8G-1S-W1-64-BK	i3-8100T	Window 10	8GB	128GB SSD	USB
E375459	EPS22H3-2UWA-1-MT-4G-1S-NO-00-BK-NS-EXP	i3-8100T	None	4GB	128GB SSD	USB
E397507	EPS22H3-2UWA-1-MT-4G-1S-W1-64-BK-NS-EXP	i3-8100T	Window 10	4GB	128GB SSD	USB
E511785	EPS22H3-2UWA-1-MT-8G-1S-NO-00-BK-NS-EXP	i3-8100T	None	8GB	128GB SSD	USB
E937919	EPS22H5-2UWA-1-MT-8G-1S-NO-00-BK	i5-8500T	None	8GB	128GB SSD	USB



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchcomputer

### EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 11 of 8

E937720	EPS22H5-2UWA-1-MT-8G-1S-W1-64-BK	i5-8500T	Window 10	8GB	128GB SSD	USB
E560404	EPS22H5-2UWA-1-MT-8G-2S-W1-64-BK	i5-8500T	Window 10	8GB	256GB SSD	USB
E417915	EPS22H5-2UWA-1-MT-6G-2S-W1-64-BK	i5-8500T	Window 10	16GB	256GB SSD	USB
E938297	EPS22H5-2UWA-1-MT-8G-1S-NO-00-BK-NS-EXP	i5-8500T	None	8GB	128GB SSD	USB
E938113	EPS22H5-2UWA-1-MT-8G-1S-W1-64-BK-NS-EXP	i5-8500T	Window 10	8GB	128GB SSD	USB



Elo Touch Solutions, Inc.  
670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchcomputer

### EloPOS Rev A

DOCUMENT: PS600353  
REV: G  
REV DATE: July 28, 2020  
Page 12 of 8

## Documentation List

Document Number	Description
MS602246	DIMENSIONAL DRAWING, EloPOS
QIG600049	QIG, EloPOS
UM600232	USER GUIDE, EloPOS
UM600233	USER GUIDE, EloPOS EU SPANISH
UM600234	USER GUIDE, EloPOS LA SPANISH
UM600235	USER GUIDE, EloPOS FRENCH
UM600236	USER GUIDE, EloPOS ITALIAN
UM600237	USER GUIDE, EloPOS GERMAN
UM600238	USER GUIDE, EloPOS RUSSIAN
UM600239	USER GUIDE, EloPOS JAPANESE
UM600240	USER GUIDE, EloPOS SIM CHINESE
MD600091	DECLARATIONS OF CONFORMITY, EloPOS

**MTBF (Mean Time Between Failures)** An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit's reliability; thus MTBF is not, and should not be construed as, a warranty measurement.

Elo Touch Solutions, Inc. its Affiliates (collectively "Elo") reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products.

Elo (logo), Elo Touch Solutions, Elo TouchSystems are trademarks