



670 N. McCarthy Blvd,
Milpitas, CA 95035
www.elotouch.com

SPECIFICATIONS

Touchmonitor ET1302L

DOCUMENT: PS600361
REV LETTER: A
REV DATE: Dec. 20, 18
PAGE NO.: 1 OF 5

Model	ET1302L
Color	Black
Diagonal Size	13.3" / 337.82 mm
Active Display Area	11.57" x 6.51" / 293.76 x165.24 mm
LCD Technology	Active matrix TFT LCD
Number of Touches	10 Touches
Touch Technology	TouchPro PCAP
Aspect Ratio	16:9
Native Resolution	1920x1080
Preset Video Timings	640 x 480 60Hz; 800 x 600 60Hz; 1024 x 768 60Hz; 1280 x 720 60Hz; 1280 x 800 60Hz, 60Hz RB; 1280 x 960 60Hz; 1280 x 1024 60Hz; 1360 x 768 60Hz; 1366 x 768 60Hz, 60Hz RB; 1440 x 900 60Hz, 60Hz RB; 1680 x 1050 60Hz, 60Hz RB; 1920 x 1080 60Hz
Number of Colors	16.7M
Brightness (typical)	Panel: 300 nits; With TouchPro PCAP: 270 nits;
Response Time (Tr + Tf) (typical)	25 msec
Viewing Angle (typical)	Horizontal: ±85° / 170° total Vertical: ±85° / 170° total
Contrast Ratio (typical)	800:1
On-Screen Display (OSD)	Accessible through switches along the bottom: Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-Position, V-Position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch on Sleep Mode, Touch Through, Energy Saver, Panel Saver, Mute, Volume, Audio Select Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese, Lockouts: OSD, Power
Mounting Options	VESA 4-hole 75mm mounting interface on rear of unit See dimensional drawings for details



670 N. McCarthy Blvd,
Milpitas, CA 95035
www.elotouch.com

SPECIFICATIONS

Touchmonitor

ET1302L

DOCUMENT: PS600361
REV LETTER: A
REV DATE: Dec. 20, 18
PAGE NO.: 2 OF 5

I/O Ports	1 x USB Type-C 1 x Audio jack (Line-in) 1 x VGA 1 x HDMI 1 x 12V D/C input 4x Micro-USB side ports (Top, Bottom, Left, Right)
Video	HDMI V1.3 Type A receptacle for HDMI input Analog VGA USB Type-C Input Video Horizontal Sync frequency range: 30 – 82K KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	Option 1 - USB Type-C Input voltage range: 15V 2.5A / 20V 2A Option 2 - External DC Adapter 12V/36W in box Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) Barrel depth) Monitor input voltage range: 12VDC +/- 5% Adapter output power connector: DC barrel plug (2.1mm (+/- 0.1mm) pin inner diameter, 5.5mm (+/- 0.05mm) barrel outer diameter, 9.5mm (+/- 0.3mm) Barrel length) Adapter input voltage range: 100-240 VAC Input frequency: 50-60 Hz Power Consumption (Typical): ON (monitor + adapter): 9.8W SLEEP (monitor + adapter): 0.46W OFF (monitor + adapter): 0.18W
Audio	2 x 1W Speakers
Weight	Unpackaged with Stand: 5.11 lbs. / 2.32 kg Unpackaged Without Stand: 2.69 lbs. / 1.22 kg Packaged with Stand: 10.19 lbs. / 4.62 kg Packaged Without Stand: 6.37 lbs. / 2.89 kg



670 N. McCarthy Blvd,
Milpitas, CA 95035
www.elotouch.com

SPECIFICATIONS

Touchmonitor ET1302L

DOCUMENT: PS600361
REV LETTER: A
REV DATE: Dec. 20, 18
PAGE NO.: 3 OF 5

Dimensions (H x W x D)	With Stand: 10.22" x 12.84" x 5.91" / 259.57mm x 326.06 mm x 150 mm Without Stand: 8.32" x 12.84" x 0.99" / 211.30mm x 326.06 mm x 25.05 mm Shipping: With Stand: 13.11" x 16.34" x 8.66" cm / 333 mm x 415 mm x 220 mm Without Stand: 11.02" x 15.95" x 6.30" cm / 280 mm x 405 mm x 160 mm
Temperature	Operating: 0° C to 40° C / 32° F to 104° F Storage: -20° C to 60° C / -4° F to 140° F
Humidity (non-condensing)	Operating: 20% - 80% Storage: 10% - 95%
Regulatory approvals and declarations	Australia RCM Canada cUL, IC China CCC Europe CE, India BIS, Japan VCCI Korea KCC Mexico CoC(NOM) Taiwan BSMI United States UL, FCC International CB RoHS, China RoHS, WEEE, REACH
Ingress Protection	IPX1 for front side
Compliance	
Warranty	3 years
Additional Service Offerings	
Extended Warranty	1 Year Extended Warranty - Elo P/N: 758588-000 2 Year Extended Warranty - Elo P/N: 930057-000 Elo Advance Unit Replacement (AUR) - Elo P/N: E67295-000
Other Features	
Sealing	No



670 N. McCarthy Blvd,
Milpitas, CA 95035
www.elotouch.com

SPECIFICATIONS

Touchmonitor ET1302L

DOCUMENT: PS600361
REV LETTER: A
REV DATE: Dec. 20, 18
PAGE NO.: 4 OF 5

Box contents	HDMI cable Touch USB Cable (USB Type-A to Type-C) Quick Install Guide EEI Label Power brick NA Power cable EU Power cable 3x Tie wraps 2x screws for cable cover(s)
--------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Part Number	Part Description	Touch Technology	Surface Treatment	Touch Interface	Color
E683204	ET1302L-2UWA-1-BL-G	TouchPro PCAP	Anti-glare	USB	Black
E683595	ET1302L-2UWA-1-BL-NS-G	TouchPro PCAP	Anti-glare	USB	Black

Options/Peripheral/Upgrades	Part #	Options/Peripheral/Upgrades	Part #
KIT,MSR,USB,ESY X Series/AAiO/02 Series	E001002	Pcap Stylus	E066148
KIT, BCR MODULE for AAiO	E093433	2D Barcode Scanner	E926356
KIT,VFD,USB,ESY X-Series	E001003	EMV Cradle for Ingenico ICMP	E200465
ELO-KIT-BOLT DOWN 6 INCH-R	E047458	EMV Cradle for Verifone E355	E201088
ELO-KIT-BOLT DOWN 12 INCH-R	E047663	KIT-EMV-BRKT-EDYNAMO	E375343
ELO-KIT-BOLT DOWN 18 INCH-R	E047864	KIT-EMV-BRKT-ING-RP457C	E586981
ELO-KIT-FLOOR STAND 5 FOOT-R	E048069	ELO-KIT-CABLE-USB-C-to-USB-C	E710364
ELO-SHELFMNT-R	E043382	ELO-KIT-CABLE-VGA-DB15-to-MICRO	E710549
ELO-POLE-MNTBRKT-R	E045151	ELO-KIT-CABLE-DVI-D-To-HDMI	E538507
		ELO-KIT-ANDROID-MEDIA-PLAYER	E611864

Document Number	Description
E893866	QIG
MS602287	Dimensional drawings ET1302L
MD600092	Regulatory certificates



670 N. McCarthy Blvd,
Milpitas, CA 95035
www.elotouch.com

SPECIFICATIONS

Touchmonitor

ET1302L

DOCUMENT: PS600361
REV LETTER: A
REV DATE: Dec. 20, 18
PAGE NO.: 5 OF 5

UM600243	User Guide – English
UM600245	User Guide – French
UM600246	User Guide – Italian
UM600247	User Guide – German
UM600248	User Guide – Spanish
UM600249	User Guide – Japanese
UM600250	User Guide – Simplified Chinese
UM600251	User Guide – Traditional Chinese
UM600252	User Guide – Korean
UM600253	User Guide – Russian