



670N McCarthy Blvd  
Milpitas, CA 95035  
www.elotouch.com

SPECIFICATIONS  
Touchmonitor  
IDS 3203L Monitor

DOCUMENT: PS600367  
REV LETTER: B  
REV DATE: Sep 16, 2020  
PAGE NO.: 1 OF 6

**TITLE: SPECIFICATIONS IDS 03 Monitor, Touchmonitor**

**NUMBER: PS600367**

**REVISION: B**

**OWNER: Engineering**

**Change History**

Rev	Author	Date	Description
A	Henry Hsu	09/01/2020	Initial release per CO-20-1453
B	Henry Hsu	09/16/2020	Update per CO-20-xxxx - Correct 3203L/4303L HDMI to V1.4 and DP to V1.2 - Remove HDR10 compatible (auto detect)
			-
			-



670N McCarthy Blvd  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchmonitor

### IDS 3203L Monitor

DOCUMENT: PS600367  
REV LETTER: B  
REV DATE: Sep 16, 2020  
PAGE NO.: 2 OF 6

<b>Model</b>	<b>ET3203L</b>
<b>Color</b>	<b>Black</b>
<b>Diagonal Size</b>	31.5" / 800.1 mm
<b>Active Display Area</b>	27.5" x 15.47" / 698.4 mm x 392.9 mm
<b>LCD Technology</b>	Active matrix TFT LCD
<b>Touch Technology &amp; Capacity</b>	TouchPro® PCAP - up to 40 touches with palm rejection and touch thru capability
<b>Touch Thru</b>	Supports up to 6mm glass/3mm plastic with up to 2 touches. Supports gloves up to 1.4mm
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	1920 x 1080 @ 60hz
<b>Preset Video Timings</b>	640x480 60Hz 800x600 56/60Hz 1024x768 60Hz 1280x720 60Hz 1280x960 60Hz 1280x1024 60Hz 1920x1080 50/60Hz
<b>Number of Colors</b>	8bit(D), 16.7Millon colors
<b>Brightness (typical)</b>	<b>Panel:</b> 450 nits <b>With PCAP:</b> 382 nits
<b>Response Time (Tr + Tf) (typical)</b>	8 msec
<b>Viewing Angle (typical)</b>	<b>Horizontal:</b> 89°/89° or 178° total <b>Vertical:</b> 89°/89° or 178° total
<b>Contrast Ratio (typical)</b>	3000:1
<b>On-Screen Display (OSD)</b>	<b>Let's Get Started:</b> Language Selection, Time Setting, Time Zone <b>Video Source Select:</b> HDMI-1, HDMI-2, DisplayPort, USB-C, Internal-PC DP, Internal-PC HDMI <b>Video Settings:</b> Video Port Discovery, Brightness, Contrast, Black Level, Sharpness and Aspect Ratio can be selected <b>Color Settings:</b> Color Temperature, Color Sensor, User Preset (for color), Picture Modes and HDMI Full Range are available in this menu. <b>Audio Settings:</b> Audio Input, Audio Output, Mute, Volume selection are available here. <b>Power:</b> Power Loss Behavior, Power Lock, Energy Saving Mode, Power Status Light options are available here <b>Time:</b> Time Set, On/Off Schedule <b>OSD Settings:</b> Recall Defaults, OSD Timer, OSD Language, OSD Lock and OSD Portrait Rotation, Touch Switch, Tabletop <b>Information:</b> Monitor, Temperature, Help and Support are available here  <b>See user manual for full details.</b>



670N McCarthy Blvd  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchmonitor

### IDS 3203L Monitor

DOCUMENT: PS600367  
REV LETTER: B  
REV DATE: Sep 16, 2020  
PAGE NO.: 3 OF 6

Mounting Options	VESA MOUNT PER MIS-F, 400 x 400mm, M6 See dimensional drawings for details
I/O Ports	HDMI 1.4 x2 USB-C (for Touch and video) RJ45 (for optional OSD remote) DisplayPort 1.2 3.5mm TRS jack (for RS232/MDC) 3.5mm Audio Headphones out Elo Edge Connect Micro USB 2.0 x4
Control Buttons	Power Video Source Selection On Screen Display
Video	2x HDCP-capable HDMI on Type A connector DisplayPort 1.2 connector USB-C connector <b>Input Video Horizontal Sync frequency range:</b> FHD: 30 – 69 KHz <b>Input Video Vertical Sync (frame rate) frequency range:</b> 24 - 64 Hz
Power	<b>Input connector (power):</b> IEC 60320-C13 <b>Input signal specifications (power):</b> 100-240VAC 50/60Hz
Power Consumption	<b>ON (monitor + AC/DC adapter):</b> 44 W <b>ON (monitor with ECMG4 + AC/DC adapter):</b> 81 W <b>SLEEP (monitor + AC/DC adapter):</b> 1.43 W <b>SLEEP (monitor with ECMG4 + AC/DC adapter):</b> 3.5 W <b>OFF (monitor + AC/DC adapter):</b> 0.29 W
Audio	<b>Speakers:</b> 2 x 5 W stereo speakers <b>Headphone output:</b> 3.5 mm TRS jack
Weight	<b>Unpackaged With ECMG4:</b> 30.8 lbs./ 13.97 Kg <b>Unpackaged Without ECMG4:</b> 26.17 lbs./ 11.87 Kg <b>Packaged Without ECMG4:</b> 33.75 lbs./ 15.31 Kg
Dimensions	30.11 " x 18.07 " x 2.25 " / 764.7 mm x 459.1 mm x 57.2 mm <b>Shipping:</b> 35.04 " x 25.2 " x 6.3 " / 890 mm x 640 mm x 160 mm
Temperature	<b>Portrait/Landscape/Tilt (<math>\leq 15^\circ</math>) Mode:</b> <b>Operating:</b> 0° C to 40° C / 32° F to 104° F <b>Storage:</b> -20° C to 60° C / -4° F to 140° F <b>Tabletop Mode:</b> <b>Operating:</b> 0° C to 35° C / 32° F to 95° F <b>Storage:</b> -20° C to 60° C / -4° F to 140° F
Humidity (non-condensing)	<b>Operating:</b> 20% - 80% <b>Storage:</b> 10% - 95% (38.7°C max wet bulb temperature)
Regulatory approvals and declarations	UL 62368-1 FCC (US) cUL, IC (Canada) CB (International safety) (IEC/EN60950-1+IEC/EN62368-1) CE (Europe) VCCI (Japan) RCM (Australia) CCC, China RoHS (China) (for TouchPro version only) IK07 and UL60950 for ball drop test
Compliance	Energy Star 8.0



670N McCarthy Blvd  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchmonitor

### IDS 3203L Monitor

DOCUMENT: PS600367  
REV LETTER: B  
REV DATE: Sep 16, 2020  
PAGE NO.: 4 OF 6

Warranty	3 years with AUR included
Extended Warranty	4 year warranty coverage + AUR - Elo P/N: E740135 5 year warranty coverage + AUR - Elo P/N: E740330 3 year warranty coverage + OSE (Continental US only) - Elo P/N: E740527 4 year warranty coverage + OSE (Continental US only) - Elo P/N: E740728 5 year warranty coverage + OSE (Continental US only) - Elo P/N: E740918
Maximum operating time	24 hours/day
Other Features	Ambient Light Sensor - changes panel color to match ambient light, Auto Wake
Sealing	Touchscreen sealed to bezel Touchscreen sealed to LCD
MTBF	50,000 hours demonstrated
Box contents	Quick Install Guide HDMI 2.0 cable (Type A plug to Type A plug) USB cable (Type A plug to Type C plug) Power cable, IEC 60320-C5 to NA plug Power cable, IEC 60320-C5 to EU/KR plug Power cable, IEC 60320-C5 to UK plug Serial 3.5mm male to Serial DB9 female cable (MDC Cable) Energy label according to EU Regulation 1062/2010



670N McCarthy Blvd  
Milpitas, CA 95035  
www.elotouch.com

## SPECIFICATIONS Touchmonitor IDS 3203L Monitor

DOCUMENT: PS600367  
REV LETTER: B  
REV DATE: Sep 16, 2020  
PAGE NO.: 5 OF 6

### Part Number List

Part Number	Part Description	UPC	Touch Technology	Surface Treatment	Touch Interface
E720061	ET3203L-2UWA-0-MT-ZB-GY-G	843173109923	TouchPro	Clear with Anti-Friction	USB-C

### Optional Accessories

Options/Peripheral/Upgrades	Part #	Options/Peripheral/Upgrades	Part #
Magnetic Stripe Reader	E001002	Wall mount	E721949
2D Barcode Reader	E926356	Stand	E722153
1D Barcode Reader	E093433		
NFC reader	E001004		
Fingerprint Reader	E001001	OSD Remote	E483757
(Replacement) Cable Kit	E141067	WebCAM IDS02	E275233
Conference Camera	E277819	ECMG4 with no OS	E227895
EMV Cradle for Ingenico ICMP	E200788	ECMG4 with Win10 LTSC	E228087
EMV Cradle for Verifone E355	E201363	ECMG4 with Win10 SAC	E725044
EMV Cradle for Ingenico RP457c with BT and USB	E710930	ECMG4 with Win10 LTSC with Montage	E898841
EMV Cradle for Ingenico RP457c with Audio Jack, BT and USB	E586981	ECMG4 with Win10 LTSC with Collaboration	E405488
EMV Cradle for MagTek eDynamo	E375343	Elo Backpack Android (supports a maximum resolution of 1920 x 1080)	E611864
Elo Huddle Kit	E380925	Elo Backpack Android 3.0 (supports a maximum resolution of 1920 x 1080)	E901355

### Future Support Accessories

Options/Peripheral/Upgrades	Part #	Options/Peripheral/Upgrades	Part #
Fingerprint Reader	E134286	3D Camera	E134699
2D Webcam	E201494	Temperature Sensor Pro	E534879
2D Barcode Scanner (SE2707)	E393160	2D Barcode Scanner (SE4720)	E384627



670N McCarthy Blvd  
Milpitas, CA 95035  
www.elotouch.com

# SPECIFICATIONS

## Touchmonitor

### IDS 3203L Monitor

DOCUMENT: PS600367  
REV LETTER: B  
REV DATE: Sep 16, 2020  
PAGE NO.: 6 OF 6

## Documentation List

Document Number	Description
QIG600066	QIG, IDS 03 Series
MS602351	DIMENSIONAL DRAWING, ET3203L
MS602352	DIMENSIONAL DRAWING, ET43x3L
MS602353	DIMENSIONAL DRAWING, ET5053L
SD608929	DRAWING, FILES MECH, 3D, 3203L
SD608285	DRAWING, FILES MECH, 3D, 43x3L
SD608928	DRAWING, FILES MECH, 3D, 5053L
UM600265	USER GUIDE, IDS 03 SERIES, ENGLISH
UM600266	USER GUIDE, IDS 03 SERIES, FRENCH
UM600267	USER GUIDE, IDS 03 SERIES, GERMAN
UM600268	USER GUIDE, IDS 03 SERIES, SPANISH
UM600269	USER GUIDE, IDS 03 SERIES, ITALIAN
UM600270	USER GUIDE, IDS 03 SERIES, RUSSIAN
UM600271	USER GUIDE, IDS 03 SERIES, SIMPLIFIED CHINESE
UM600303	USER GUIDE, IDS 03 SERIES, TRADITIONAL CHINESE
UM600272	USER GUIDE, IDS 03 SERIES, JAPANESE
UM600304	USER GUIDE, IDS 03 SERIES, KOREAN

**MTBF (Mean Time Between Failures)** An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit's reliability; thus MTBF is not, and should not be construed as, a warranty measurement.

Copyright © 2020 Elo Touch Solutions, Inc. All Rights Reserved.

No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, including, but not limited to, electronic, magnetic, optical, chemical, manual, or otherwise without prior written permission of Elo Touch Solutions, Inc.

### Disclaimer

The information in this document is subject to change without notice. Elo Touch Solutions, Inc. and its affiliates (collectively "Elo") makes no representations or warranties with respect to the contents herein, and specifically disclaims any implied warranties of merchantability or fitness for a particular purpose. Elo reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Elo to notify any person of such revisions or changes.

### Trademark Acknowledgments

AccuTouch, CarrollTouch, Elo (logo), Elo Touch Solutions, Elo TouchSystems, IntelliTouch, iTouch are trademarks of Elo and its Affiliates. Windows is a trademark of Microsoft Corporation.