PRODUCT SPEC, KIT, 2DBCR, USB, SE2707

PRODUCT: *2DBCR*
DOCUMENT: PS600461
REV LETTER: 0
REV DATE: Dec. 6, 20
PAGE NO.: 1 OF 2

ēlo

670 N. Milpitas Blvd Suite 100
Milpitas, CA 95035
Phone: 1-800-ELO-TOUCH (356-8682)
www.elotouch.com

Model	E393160
Color	Black
Compatibility	I-Series for Android or Windows (10, 15, 22) AiO Touchscreen Signage EloPOS (15, 15.6, 22) AiO POS Terminals 02-Series Monitors (1002L, 1302L, 1502L, 1902L, 2002L, 2202L, 2402L, 2702L) Touchscreen Monitors IDS 02-Series (3202L, 4202L, 4602L, 5502L) Touchscreen Signage IDS 53-Series (5553L, 6553L)
Product Dimensions	118.5mm x 26.6mm x 160mm (4.67" x 1.05" x 6.30")
Barcode Engine	SE2707
Standard Configuration	SNAPI with Imaging Interface Presentation Mode
Supported Terminal Modes	SNAPI Keyboard HID
Resolution	640 x 400
Illumination & Aiming	Red LED illumination, Orange LED aimer
Ideal Scan Range	1.5-19.5 in. (3.8cm to 49.5cm) (depends on barcode quality, size and evironmental conditions)
Supported Symbologies	**1D symbologies: All major 1D** **2D symbologies: All major 2D including:** **PDF417, MicroPDF417, Datamatrix, QR Code,** **Micro QR Code, Aztec** **MaxiCode; Grid Matrix**
Viewing Angle	Horizontal: 42°, Vertical: 28°
Beeper Support	Yes
Weight	Unpackaged: 0.022 kg (0.049 lbs) Packaged: 0.12 kg (0.26 lbs)
Shipping Dimensions	175mm x 114mm x 69mm (6.89" x 4.49" x 2.72")
Temperature	Operating: 10° C to 40° C (50° F to 104° F) Storage: 0° C to 50° C (32° F to 122° F)
Humidity (non-condensing)	Operating: 20% - 80% Storage: 10% - 90%

PRODUCT SPEC,
KIT, 2DBCR, USB, SE2707

PRODUCT: *2DBCR*
DOCUMENT: PS600461
REV LETTER: 0
REV DATE: Dec. 6, 20
PAGE NO.: 2 OF 2

670 N. Milpitas Blvd Suite 100
Milpitas, CA 95035
Phone: 1-800-ELO-TOUCH (356-8682)
www.elotouch.com

Warranty	2 years
Kit Contents	2D Barcode Scanner 2 Mounting screws 2 Mylar screw covers QIG

Part Number	Region	Description
E393160	Worldwide	KIT, 2DBCR, USB, SE2707, EDGE CONNECT