



## SPECIFICATIONS Touchmonitor 1717L

PRODUCT: 1717  
TouchMonitor  
DOCUMENT: PS600465  
REV LETTER A  
REV DATE: Jan. 26, 21  
PAGE NO.: 1 OF 4

670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
Phone: 1-800-ELO-TOUCH (356-8682)  
www.elotouch.com

Deleted: Jan. 12, 21

|                                   |   |
|-----------------------------------|---|
| <b>Model</b>                      | <b>1717L</b>  |
| Color                             | Black or white  |
| Active Display Area               | 13.3" x 10.64" / 337.92mm x 270.34mm  |
| Dimensions                        | 15.43" x 8.38" x 14.24" / 391.9mm x 215.4mm x 361.6mm<br>See dimensional drawings for details   |
| LCD Technology                    | Active matrix TFT LCD   |
| Diagonal Size                     | 17"   |
| On-Screen Display (OSD)           | Accessible through switches along the bottom.<br><br><b>Controls:</b> Menu, Up, Down, Select<br><b>Settings:</b> Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Sharpness, Color Temperature, OSD Timeout, OSD Language, Recall Defaults<br><b>Languages:</b> English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese<br><b>Lockouts:</b> OSD, Power |
| Mounting Options                  | VESA 4-hole 75mm mounting interface on rear of unit<br>3-hole threaded mounting on bottom of stand<br>See dimensional drawings for details  |
| Aspect Ratio                      | 5:4   |
| Native Resolution                 | 1280 x 1024   |
| Preset Video Timings              | 640x480 @60Hz,75Hz<br>720x400 @70Hz<br>800x600 @56Hz, 60Hz,75Hz<br>1024x768 @60Hz,75Hz<br>1280x1024 @60Hz,75Hz  |
| Number of Colors                  | 16.7 million  |
| Brightness (typical)              | LCD Panel: 250 nits<br>with IntelliTouch Zero-Bezel: 225 nits<br>with IntelliTouch: 225 nits<br>with AccuTouch: 200 nits  |
| Response Time (Tr + Tf) (typical) | 5 msec  |
| Viewing Angle (typical)           | Horizontal: $\pm 85^\circ$ / $170^\circ$<br>Vertical: $\pm 80^\circ$ / $160^\circ$  |
| Contrast Ratio (typical)          | 1000:1  |



SPECIFICATIONS  
Touchmonitor  
1717L

PRODUCT: 1717  
TouchMonitor  
DOCUMENT: PS600465  
REV LETTER A  
REV DATE: Jan. 26, 21  
PAGE NO.: 2 OF 4

670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
Phone: 1-800-ELO-TOUCH (356-8682)  
www.elotouch.com

Deleted: Jan. 12, 21

|                                       |   |
|---------------------------------------|---|
| Video                                 | Analog VGA on Female DB-15 connector<br><b>Digital HDMI on Type A receptacle</b><br>Input Video Horizontal Sync frequency range: 31.5-80KHz<br>Input Video Vertical Sync (frame rate) frequency range: 56-75Hz  |
| Power                                 | <b>Monitor AC input power connector</b> : IEC 60320 C6<br><b>Monitor AC input voltage specifications</b> : 100-240VAC, 50/60Hz<br><br><b>Monitor DC input power connector</b> : Coaxial power jack (2.0mm pin outer diameter, 6.4mm barrel inner diameter)<br><b>Monitor DC input voltage specifications</b> : 12VDC +/- 5%<br><br><b>Note: Optional AC-DC power adapter sold for this monitor:</b><br><b>AC input connector</b> : IEC 60320 C14<br><b>AC input voltage specification</b> : 100-240VAC, 50/60Hz<br><br><b>Power Consumption (Typical):</b><br><b>ON (monitor only): 11.5W</b><br><b>SLEEP (monitor only): 1.2W</b><br><b>OFF (monitor only): 0.4W</b> |
| Weight                                | <b>Unpackaged</b> : 11.9 lbs / 5.4 Kg<br><b>Packaged</b> : 18.3lbs / 8.3 Kg   |
| Shipping Dimensions                   | 20.12" x 9.17" x 20.08" / 511mm x 233mm x 510mm   |
| Temperature                           | Operating: 0° C to 40° C / 32° F to 104° F<br>Storage: -20° C to 60° C / -4° F to 140° F  |
| Humidity (non-condensing)             | Operating: 20% to 80%<br><b>Storage: 10% to 95%</b>   |
| Regulatory approvals and declarations | Argentina S-mark<br>Australia RCM<br>Canada cUL, IC<br>China CCC<br>Europe CE<br>Japan VCCI<br>Korea KCC, e-Standby<br><b>Mexico NOM</b><br>Taiwan BSMI Mark<br>United States UL, FCC<br>International CB<br>RoHS, China RoHS, WEEE   |



**SPECIFICATIONS**  
Touchmonitor  
1717L

PRODUCT: 1717  
TouchMonitor  
DOCUMENT: PS600465  
REV LETTER A  
REV DATE: Jan. 26, 21  
PAGE NO.: 3 OF 4

670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
Phone: 1-800-ELO-TOUCH (356-8682)  
www.elotouch.com

Deleted: Jan. 12, 21

|                             |  |
|-----------------------------|--|
| Warranty                    | 3 years<br>4 year warranty coverage - Elo P/N: E898247<br>5 year warranty coverage - Elo P/N: E898449<br>3 year warranty coverage + AUR - Elo P/N: E898648<br>4 year warranty coverage + AUR - Elo P/N: E894921<br>5 year warranty coverage + AUR - Elo P/N: E895125 |
| MTBF                        | 50,000 hours demonstrated  |
| Box contents                | Quick Install Guide<br>Japan Class-B TM info sheet<br>User Manual CD<br>VGA Cable (DB-15 male to DB-15 male)<br>Touch USB Cable (USB Type A plug to USB Type B plug)<br>power cable, IEC 60320-C5 to NA/EU plug<br>Stand Base assembly<br>Filler Plate<br>HDMI cable |
| Replacement DC Power Supply | The monitor may be powered with DC voltage. A optional 12V DC power brick, Elo P/N: E005277, is available at additional cost.  |
| AC Power Cable              | North American & EU power cables included. UK AC power cables included with P/Ns available for EMEA.<br><br>China: E501749<br>UK: E540272  |
| Touch/Video Cables          | Detachable touch and video cables are included   |
| Optional Peripherals        | Magnetic Stripe Reader (Black MSR) – Elo P/N: E500356.   |
| Stands, Mounts & Kits       | 1717L VESA Mount Plate (White) - Elo p/n: E000421<br>1717L VESA Mount Plate (Black) - Elo p/n: E000405<br>1717 Replacement Stand (White) - Elo p/n: E061177<br>1717 Replacement Stand (Black) - Elo p/n: E904304   |

Commented [JG1]: Remove

| Part Number | Part Description       | Touch Technology     | Surface Treatment | Touch Interface  | Color | Availability |
|-------------|------------------------|----------------------|-------------------|------------------|-------|--------------|
| E649473     | ET1717L-7CWB-1-BL-ZB-G | AccuTouch Zero Bezel | Anti-glare        | USB/Serial combo | Black | Worldwide    |
| E877820     | ET1717L-7CWB-1-BL-G    | AccuTouch            | Anti-glare        | USB/Serial combo | Black | Worldwide    |



## SPECIFICATIONS Touchmonitor 1717L

670 N. McCarthy Blvd., Suite 100  
Milpitas, CA 95035  
Phone: 1-800-ELO-TOUCH (356-8682)  
[www.elotouch.com](http://www.elotouch.com)

PRODUCT: 1717  
TouchMonitor  
DOCUMENT: PS600465  
REV LETTER A  
REV DATE: Jan. 26, 21  
PAGE NO.: 4 OF 4

Deleted: Jan. 12, 21

|         |                        |                            |            |                     |       |           |
|---------|------------------------|----------------------------|------------|---------------------|-------|-----------|
| E017030 | ET1717L-8CWB-1-BL-ZB-G | IntelliTouch<br>Zero-Bezel | Anti-glare | USB/Serial<br>combo | Black | Worldwide |
| E179069 | ET1717L-8CWB-0-BL-ZB-G | IntelliTouch<br>Zero-Bezel | Clear      | USB/Serial<br>combo | Black | Worldwide |
| E077464 | ET1717L-8CWB-1-BL-G    | IntelliTouch               | Anti-glare | USB/Serial<br>combo | Black | Worldwide |

| Document Number | Description                      |
|-----------------|----------------------------------|
| MS601505        | Dimensional drawings             |
| MD600055        | Regulatory certificates          |
| SW602763        | User Guide – English             |
| SW602764        | User Guide – French              |
| SW602765        | User Guide – Italian             |
| SW602766        | User Guide – German              |
| SW602767        | User Guide – Spanish             |
| SW602768        | User Guide – Japanese            |
| SW602769        | User Guide – Simplified Chinese  |
| SW602770        | User Guide – Traditional Chinese |
| SW602771        | User Guide – Korean              |

**MTBF (Mean Time Between Failures)** An MTBF measurement is based on a statistical sample and is not intended to predict any one specific unit's reliability; thus MTBF is not, and should not be construed as, a warranty measurement.