

SPECIFICATIONS ELO-HUB

PRODUCT: *ELO-HUB* DOCUMENT: PS600441 REV LETTER: A REV DATE: 6/27/2020 PAGE NO.: 1 OF 4

670 N. McCarthy Blvd Milpitas, CA 95035 Phone: 1-800-ELO-TOUCH (356-8682) www.elotouch.com

TITLE: SPECIFICATIONS ELO-HUB

NUMBER: PS600441

REVISION: A

OWNER: Engineering

Change History				
Rev	Author	Date	Description	
Α	Michael Rally	5/27/2020	Initial release	

ēlo

SPECIFICATIONS ELO-HUB

PRODUCT: *ELO-HUB* DOCUMENT: PS600441 REV LETTER: A REV DATE: 6/27/2020 PAGE NO.: 2 OF 4

670 N. McCarthy Blvd Milpitas, CA 95035 Phone: 1-800-ELO-TOUCH (356-8682) www.elotouch.com

ELO-HUB (E216030)	
Audio	
Microphone Array	4 Microphone Adaptive Beamforming circular array
Microphone Sensitivity	70dBA @ 1kHz
Microphone Frequency Range	100Hz – 15kHz
Acoustic Echo Cancellation	Up to 50dB (max)
Noise Suppression	15dB (max)
Speaker Output	12 Watts (peak)
Speaker Frequency Range	100Hz – 15kHz
Video	
Supported Video Resolutions	4K UHD 3840x2160@30Hz FHD 1920x1080@60Hz HD 1280x720@60Hz VGA 640x480@60Hz
Aspect Ratio	4:3, 16:9
Supported Frame Rates	29.97Hz, 30Hz, 50Hz, 59.94Hz, 60Hz
I/O Ports	HDBaseT RJ45 Jack, HDMI, USB-C, USB 2.0 Type A
Color Depth	24 bpp with 4:4:4 pixel format
HDBaseT installation cable length	35 meters(max) for 3840x2160@30Hz 60 meters(max) for 1920x1080@60Hz
Controls	Call – Answer Call, End Call, Mute, Volume Control Buttons Meeting – Meeting Control, Start Meeting Buttons
Packaging	
Weight w/Packaging (1 pcs/box)	2.8 kg (6.17 lbs)
Weight w/o Packaging	1.7 kg (3.75 lbs)
Module Dimensions	Width 194.3 mm (7.65 in) Length: 159.0 mm (6.25 in) Height: 142.0 mm (5.59 in)
Shipping Dimensions (individual unit)	Width: 257 mm (10.12 in) Height: 256 mm (10.08 in) Length: 294 mm (11.58 in)
Compatibility	6553L and 5553L with ECMG4 (E405488)
Agency Certifications	FCC (US) - Class A IC (Canada) CE (Europe) - Class A VCCI (Japan) - Class A C-Tick (Australia) - Class A CCC, China RoHS (China)
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 50°C (-4°F to 122°F)
Humidity (non-condensing)	Operating: 20% to 80% Storage: 10% to 90%

ēlo

SPECIFICATIONS ELO-HUB

PRODUCT: *ELO-HUB* DOCUMENT: PS600441 REV LETTER: A REV DATE: 6/27/2020 PAGE NO.: 3 OF 4

670 N. McCarthy Blvd Milpitas, CA 95035 Phone: 1-800-ELO-TOUCH (356-8682) www.elotouch.com

MTBF	30,000 hours demonstrated
Standard Warranty	Elo Hub: 3-year
What's in the Box	Elo Hub Receive board (Rx) with anti-ESD mylar pre-attached in an ESD bag Rx board cover for 6553L Rx board cover for 5553L 3x screws (to connect the Rx board to the 6553L/5553L) 4x screws (to connect the Rx board to the Rx cover) 5 meter Cat6 Cable 1.8 meter HDMI Cable 1.8 meter USB-C Cable with Type A attachment 2x Cable Security Brackets with 2x screws Quick Install Guide Quick User Guide (Laminated)

Part Number	Part Description	UPC Code
E216030	ELO-KIT-CONFERENCE-HUB	843173102535

Document Number	Description
QIG600108	QUICK INSTALL GUIDE, ELO HUB
UM600501	QUICK USER GUIDE, ELO HUB
MS602687	DIMENSIONAL DRAWING, ELO HUB

Copyright © 2020 Elo Touch Solutions, Inc. All Rights Reserved.

No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, including, but not limited to, electronic, magnetic, optical, chemical, manual, or otherwise without prior written permission of Elo Touch Solutions, Inc.

Disclaimer

The information in this document is subject to change without notice. Elo Touch Solutions, Inc. and its affiliates (collectively "Elo") makes no representations or warranties with respect to the contents herein, and specifically disclaims any implied warranties of merchantability or fitness for a particular purpose. Elo reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Elo to notify any person of such revisions or changes.

Trademark Acknowledgments



SPECIFICATIONS ELO-HUB

PRODUCT: *ELO-HUB* DOCUMENT: PS600441 REV LETTER: A REV DATE: 6/27/2020 PAGE NO.: 4 OF 4

670 N. McCarthy Blvd Milpitas, CA 95035 Phone: 1-800-ELO-TOUCH (356-8682) www.elotouch.com

AccuTouch, CarrollTouch, Elo (logo), Elo Touch Solutions, Elo TouchSystems, IntelliTouch, iTouch are trademarks of Elo and its Affiliates. Windows is a trademark of Microsoft Corporation.